

In the Specification:

Please amend the specification as indicated below.

Paragraph 24 on page 7:

E1
Four-way stretchable material layer 112 has top surface 110 and a bottom surface 114, such that top surface 110 of 4-way stretchable material layer 112 conforms to and is permanently affixed to bottom surface 106 of skin layer 104. Four-way stretchable material layer 112 may be comprised of any material that can simultaneously stretch in four directions such as a polyester material; an example is MYLAR®. Bottom surface 114 of 4-way stretchable material layer 112 is releasably attached to the railing or hand support system by a layer of releasable adhesive 116. Releasable adhesive 116 completely covers from edge to edge and is affixed to 4-way stretchable material layer 112 and provides releasable adhesion to the railing or hand support system. Releasable adhesive 116 provides secure adhesion to the railing or hand support system but may be removed with a minimal amount of effort by peeling wrap-around advertising surface 100 off the railing or hand support system, etc. Any adhesive having the characteristics of being secured to the railing as well as being easily removed can be utilized. ~~Any acrylic-based adhesive, rubber-based adhesive, or silicone-based adhesive can be utilized;~~ a preferred example of a releasable adhesive is FLEXCON® V-58.

Paragraph 28 on page 9:

E2
Backing layer 212 has a top surface 210 and a bottom surface 214, such that top surface 210 of backing layer 212 conforms to and is affixed to bottom

42
surface 206 of skin layer 204. Backing layer 212 may be comprised of any material suitable for providing support including open cell foam, closed cell foam, felt, paper or rubber. Bottom surface 214 of backing layer 212 is permanently adhered to the top surface 218 of 4-way stretchable material layer 220. The permanent adhesive 216 attaching bottom surface 214 of backing layer 212 to top surface 218 of 4-way stretchable material layer 220 can be any resin based permanent adhesive known in the art which will permanently bond the surfaces, an example of a resin based adhesive is FLEXCON® V-402. Four-way stretchable material layer 220 has the ability to stretch in all directions simultaneously such as a polyester material; an example is MYLAR®. Bottom surface 222 of 4-way stretchable material layer 220 is releasably attached to the railing or hand support system by releasable adhesive 224. Releasable adhesive 224 is affixed to and completely covers 4-way stretchable material layer 220 from edge to edge and provides releasable adhesion to the railing or hand support system. Releasable adhesive 224 provides secure adhesion to the railing or hand support system but may be removed with a minimal amount of effort by peeling wrap-around advertising surface 200 off the railing or hand support system. Any adhesive having the characteristics of being secured to the railing as well as being easily removed can be utilized. ~~Any acrylic-based adhesive, rubber-based adhesive, or silicone-based adhesive can be utilized;~~ a A preferred example of a releasable adhesive is FLEXCON® V-58.
